



 PRODUCT-DETAILS

2CSK1214CH

Removable anti-blackout light, 230V~. Charge reserve 4.5 h and recharge time 10-20h. To be combined with 230V~ plug sockets; particularly recommended for codes 2CSK1108CH and 2CSK1109CH. LED not exchangeable White - Chiara

General Information	
Product ID	2CSK1214CH
EAN	8012542032052
Catalog Description	Removable anti-blackout light, 230V~. Charge reserve 4.5 h and recharge time 10-20h. To be combined with 230V~ plug sockets; particularly recommended for codes 2CSK1108CH and 2CSK1109CH. LED not exchangeable White - Chiara
Long Description	Removable anti-blackout light, 230V~. Charge reserve 4.5 h and recharge time 10-20h. To be combined with 230V~ plug sockets; particularly recommended for codes 2CSK1108CH and 2CSK1109CH.

Installation

Instructions and Manuals	2CSC600290D0201
Mounting Type	Surface Mounted

Technical

Data Sheet, Technical Information	2CSC600290D0201
-----------------------------------	-----------------

Function	Escape route lighting
Number of Poles	2
Number of Lamps	1
Number of Lighting Heads	1
Functional Testing Capability	Automatic Self Test
Wiring Configuration	Wiring system: Continuous circuit/emergency circuit Type of wiring: Ending
Connection Type	Pluggable
Lamp Type	LED not exchangeable
Light Distribution Type	Diffuser Lens Optic Panel
Type of Indicator	Only single-sided
Cover Material	Plastic, Transparent
Illumination	Non-illuminated
Illuminance	Standby Mode 7.54 lm
Battery Chemical Composition	Nickel-Metal Hydride
Service Life	L70/B10at25CEL 4.5 hour L70/B50at25CEL 4.5 hour L80/B10at25CEL 4.5 hour L80/B50at25CEL 4.5 hour L90/B10at25CEL 4.5 hour L90/B50at25CEL 4.5 hour 3000...3000 K

Electrical

Rated Voltage (U _r)	230...230 V
Input Voltage Type	AC
	10 W
Power Supply Type	Peripheral (Individual Battery)

Design

Design Range	Chiara
Surface Finishing	Basic
Housing Material	Plastic
Material	Plastic
Color	White
Housing Color	White

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
---	-----------------

Environmental

Ambient Temperature	IEC62722-2-1 5 ... 40 °C
Degree of Protection	IP20
Protection Class	Isolated (Class II)

Dimensions

Width in Number of Modular Spacings	2
Product Net Width	44 mm
Product Net Height	43 mm
Product Net Depth / Length	50 mm
Product Net Weight	0.004 kg
Built-In Depth (t ₂)	20 mm

Certificates and Declarations

Declaration of Conformity - CE	No declaration needed
--------------------------------	-----------------------

Classifications

ETIM 9	EC001957 - Emergency luminaire
WEEE Category	3. Lamps
WEEE B2C / B2B	Business To Consumer

Categories

Low Voltage Products and Systems → Wiring Accessories - Light Switch Ranges → Cover Plates and Control Elements → Light & Signalization



360°