




---

 PRODUCT-DETAILS

## 2CSK1306CH

Automatic MCB, 1P+N, C16, breaking capacity 3kA White - Chiara




---

### General Information

|                     |  |
|---------------------|--|
| Product ID          | 2CSK1306CH   |
| EAN                 | 8012542006756  |
| Catalog Description | Automatic MCB, 1P+N, C16, breaking capacity 3kA White - Chiara |
| Long Description    | Automatic MCB, 1P+N, C16, breaking capacity 3kA                |

---

### Installation

|                          |                 |
|--------------------------|-----------------|
| Instructions and Manuals | 2CSC600290D0201 |
|--------------------------|-----------------|

---

### Technical

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 2CSC600290D0201 |
| Energy Limiting Class             | 3               |
| Number of Poles                   | 1               |
| Number of Protected Poles         | 1               |

|                       |   |
|-----------------------|---|
| Illumination          | Non-illuminated   |
| Accessories Available | Yes   |
| Connecting Capacity   | Rigid 6 ... 6 mm <sup>2</sup><br>Flexible 6 ... 6 mm <sup>2</sup> |

## Electrical

|   |                           |
|---|---------------------------|
| Tripping Characteristic                             | C                         |
| Rated Operational Voltage                           | acc. to IEC 60947-2 230 V |
| Rated Insulation Voltage (U <sub>i</sub> )          | 2000 V                    |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> ) | 4 kV                      |
| Input Voltage Type                                  | AC                        |
| Rated Current (I <sub>n</sub> )                     | 16 A                      |
| Rated Short-Circuit Capacity                        | (230 V) 3 kA              |
| Rated Frequency (f)                                 | 50...60 Hz                |
| Overvoltage Category                                | III                       |

## Design

|                   |         |
|-------------------|---------|
| Design Range      | Chiara  |
| Surface Finishing | Basic   |
| Material          | Plastic |
| Color             | White   |

## Material Compliance

|   |                 |
|---|-----------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |
|---|-----------------|

## Environmental

|                         |                      |
|-------------------------|----------------------|
| Ambient Air Temperature | Operation -5...40 °C |
| Degree of Protection    | IP20                 |
| Pollution Degree        | 2                    |

## Dimensions

|                                     |          |
|-------------------------------------|----------|
| Width in Number of Modular Spacings | 1        |
| Product Net Width                   | 0.05 m   |
| Product Net Height                  | 25 mm    |
| Product Net Depth / Length          | 50 mm    |
| Product Net Weight                  | 0.006 kg |
| Built-In Depth (t <sub>2</sub> )    | 56 mm    |

---

## Certificates and Declarations

---

Declaration of  
Conformity - CE

No declaration needed

---

---

## Classifications

---

ETIM 9

EC000042 - Miniature circuit breaker (MCB)

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

WEEE B2C / B2B

Business To Consumer

---

---

## Categories

---

Low Voltage Products and Systems → Wiring Accessories - Light Switch Ranges → Cover Plates and Control Elements → Protection Devices



360°