

## PRODUCT-DETAILS

## HA-M-0.6.1

## HA-M-0.6.1 Heating Actuator, 6-fold, 230 V, MDRC



| General Information                     |   |
|---|---|
| Extended Product Type                   | HA-M-0.6.1  |
| Product ID                              | 2CDG510008R0011   |
| EAN                                     | 4016779941815   |
| Catalog Description                     | HA-M-0.6.1 Heating Actuator, 6-fold, 230 V, MDRC  |
| Long Description                        | For controlling thermoelectric actuating drives in heating/cooling systems. The outputs are protected against short-circuit and overload. The bus can be connected via enclosed terminal block. |
|   |   |
| Installation                            |   |
| Installation Instructions and Manuals   | 2CDG941147P0003   |
|   | 2CDG941147P0003<br>DIN-Rail   |
| Instructions and Manuals                |   |
| Instructions and Manuals  Mounting Type |   |

Compatible Bus Systems

free@home (TP)

HA-M-0.6.1 2/3

| Manipulated Variable                       | Switching free@home   |
|--|---|
| Product Range  Manual Operation            | No  |
| Number of Batteries                        | 0   |
| Electrical                                 |   |
| Voltage Range                              | 230 V AC  |
| Output Voltage (U <sub>out</sub> )         | 230 V AC  |
| Maximum Switching Current                  | 0.75 A  |
| Output Current Maximum (I <sub>out</sub> ) | 0.16 A  |
| Power Loss                                 | 2 W   |
| Design                                     |   |
| Color                                      | grey  |
|  |   |
| Material Compliance                        |   |
| RoHS Information                           | 2CDK508141D2701   |
| RoHS Status                                | Following EU Directive 2011/65/EU   |
| REACH Declaration                          | 9AKK108468A9644   |
| REACH Information Conflict Minerals        | False - does not contains substances > 0.1 mass percentage<br>9AKK108468A3363 |
| Reporting Template (CMRT)                  | 3AK 100400A3303   |
| SCIP                                       | be8a1f38-ffb3-4655-8caa-8b1ae02ea28b Germany (DE)                             |
| Environmental                              |   |
| Degree of Protection                       | IP20  |
| <u>Secrete of Protection</u>               | 11 20   |
| Dimensions                                 |   |
| Width in Number of<br>Modular Spacings     | 4   |
| Product Net Width                          | 72 mm   |
| Product Net Height                         | 90 mm   |
| Product Net Depth / Length                 | 64.5 mm   |
| Product Net Weight                         | 0.14 kg   |
| <u>Dimension Diagram</u>                   | 2CDC072033F0015   |
| Certificates and Declarations              |   |
| CB Certificate                             | 9AKK107991A3213   |
| Declaration of Conformity - CE             | 2CDK508141D2701   |
| Classifications                            |   |
| ETIM 9                                     | EC001586 - Heating actuator for bus system                                    |
| LIIW J                                     | ECOUTION - Healing actuator for bus system                                    |

HA-M-0.6.1 3/3

| eClass                     | V11.0 : 27143147   |
|----------------------------|--|
| UNSPSC                     | 39121801   |
| Object Classification Code | <u>A</u>   |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B             | Business To Consumer                                       |

## Categories

 $\mbox{Low Voltage Products and Systems} \rightarrow \mbox{Building and Home Automation Solutions} \rightarrow \mbox{free@home} \rightarrow \mbox{Heating, Ventilation and Air Conditioning} \rightarrow \mbox{Valve Drive Actuators}$ 





