



PRODUCT-DETAILS

CM-IWS.2S

CM-IWS.2S Insulation monitoring relay 1c/o, 1-100kOhm, 24-240VAC/DC



General Information

Extended Product Type	CM-IWS.2S
Product ID	1SVR730670R0200
EAN	4016779852616
Catalog Description	CM-IWS.2S Insulation monitoring relay 1c/o, 1-100kOhm, 24-240VAC/DC
Long Description	The CM-IWS.2S serves to monitor insulation resistance in accordance with IEC 61557-8 in unearthed IT AC systems with a voltage up to 400 V AC. The CM-IWS.2 can be configured to the requirements of the applications and therefore used multi-functional.

Ordering

EAN	4016779852616
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical	2CDC112196D0201
-----------------------	-----------------

Information

Instructions and Manuals	1SVC730550M0001
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	22.5 mm
Product Net Height	85.6 mm
Product Net Depth / Length	103.7 mm
Product Net Weight	0.141 kg

Technical

Function	Unearthed AC systems Up to 400 V AC
Measuring Range	1 ... 100 k Ω
Rated Control Supply Voltage (U_s)	24 ... 240 V AC/DC
Rated Frequency (f)	Measuring Circuit DC Hz Measuring Circuit 15 ... 400 Hz Supply Circuit 50/60 Hz
Output	1 c/o (SPDT) contact
Terminal Type	Screw Terminals
Rated Operational Current AC-12 (I_e)	(230 V) 4 A
Rated Operational Current AC-15 (I_e)	(230 V) 3 A
Rated Operational Current DC-12 (I_e)	(24 V) 4 A
Rated Operational Current DC-13 (I_e)	(24 V) 2 A
Minimum Switching Capacity	24 V 10 mA
Rated Impulse Withstand Voltage (U_{imp})	Measuring Circuit / Output Circuit 6 kV Supply Circuit / Measuring Circuit 6 kV Supply Circuit / Output Circuit 6 kV
Rated Insulation Voltage (U_i)	Measuring Circuit / Output Circuit 400 V Supply Circuit / Measuring Circuit 400 V Supply Circuit / Output Circuit 300 V
Degree of Protection	Housing IP50 Terminals IP20
Overvoltage Category	III
Pollution Degree	3
Short-Circuit Protective Devices	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
System Leakage Capacitance (C_E)	10 μ F
Electrical Durability	AC-12 100000 cycle
Mechanical Durability	30000000 cycle
Connecting Capacity	Flexible with Ferrule 1x 0.5 ... 2.5 mm ² Flexible with Ferrule 2x 0.5 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.5 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm ² Flexible 1x 0.5 ... 2.5 mm ² Flexible 2x 0.5 ... 1.5 mm ² Rigid 1x 0.5 ... 4 mm ²

	Rigid 2x 0.5 ... 2.5 mm ²
Tightening Torque	0.6 ... 0.8 N·m
Wire Stripping Length	8 mm
Recommended Screw Driver	0.8 x 4
Mounting Position	1 ... 6
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Standards	CAN/CSA C22.2 No.14 IEC/EN 63000 IEC/EN 61326-2-4 IEC/EN 61557-1 IEC/EN 61557-8 UL 508

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible 1x 18-14 AWG Flexible 2x 18-16 AWG Rigid 1x 20-12 AWG Rigid 2x 20-14 AWG
Tightening Torque UL/CSA	7.08 in·lb
Pilot Duty UL/CSA	B300
Flammability According to UL94	V-0

Environmental

Ambient Air Temperature	Operation -25 ... +60 °C Storage -40 ... +85 °C
Maximum Operating Altitude Permissible	Without Derating 2000 m

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SVD981001-4501
RoHS Information	1SVD981001-4401
RoHS Status	Following EU Directive 2011/65/EU
Toxic Substances Control Act - TSCA	2CMT2023-006536

Circular Value

End of Life Instructions	1SAC200290H0001
--------------------------	-----------------

Certificates and Declarations

CB Certificate	CB_DK-30302-A1-UL
CCC Certificate	CCC_2010010303438770

CQC Certificate	CQC2010010303438770
cULus Certificate	cULus508_20120727-E140448
Declaration of Conformity - CCC	2020980303000184
Declaration of Conformity - CE	1SVD981011-00
Declaration of Conformity - UKCA	1SVD981011-10
DNV GL Certificate	DNV_GL_TAA000017C

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	97 mm
Package Level 1 Depth / Length	30 mm
Package Level 1 Height	109 mm
Package Level 1 Gross Weight	0.166 kg
Package Level 1 EAN	4016779852616

Classifications

Object Classification Code	B
ETIM 7	EC001444 - Insulation and earth fault monitoring relay
ETIM 8	EC001444 - Insulation and earth fault monitoring relay
ETIM 9	EC001444 - Insulation and earth fault monitoring relay
eClass	V11.0 : 27371807
UNSPSC	39122331
E-Number (Finland)	2712262
E-Number (Sweden)	3860656

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Insulation Monitors

