




---

 PRODUCT-DETAILS

# DS201 L H C40 AC30

## DS201 L H C40 AC30 Residual Current Circuit Breaker with Overcurrent Protection




---

**General Information**

Extended Product Type	DS201 L H C40 AC30
Product ID	2CSR245073R1404
EAN	8012542354413
Catalog Description	DS201 L H C40 AC30 Residual Current Circuit Breaker with Overcurrent Protection
Long Description	The DS201 L H series is a 1P+N RCBO in two-modules width for the protection of end user single-phase circuits against overload and short-circuit currents; protection against the effects of sinusoidal alternating earth fault currents; protection against indirect contacts and additional protection against direct contacts.

---

**Technical**

Standards	EN 61009-1 EN 61009-2-1
Tripping Characteristic	C
Type of Residual Current	Type AC
Rated Operational Voltage	acc. to IEC 60898-1 230 V
Rated Insulation Voltage (U <sub>i</sub> )	acc. to IEC/EN 60664-1 500 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	4 kV
Dielectric Test Voltage	2 kV

Input Voltage Type	AC
Rated Current ( $I_n$ )	40 A
Rated Residual Current	30 mA
Rated Short-Circuit Capacity	4.5 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	6 kA
Rated Conditional Short-Circuit Current ( $I_{nc}$ )	6 kA
Rated Service Short-Circuit Breaking Capacity, in % of $I_{cu}$ ( $I_{cs}$ )	4.5 kA
Maximum Surge Current	0.25 kA
Leakage Current Type	AC
Frequency (f)	50/60 Hz
Rated Frequency (f)	50 Hz
Power Loss	Average per Pole 4.6 W Phase Pole 5.0 W Neutral Pole 4.1 W Total 9.1 W
Power Supply Connection	Arbitrary
Energy Limiting Class	3
Electrical Endurance	10000 cycle
Mechanical Endurance	20000 cycle
Number of Protected Poles	1
Number of Poles	2
Operating Characteristic	Instantaneous
Overvoltage Category	III
Position of Neutral Terminals	Right
Earthing Switch Type	Undelayed
Options Provided	None
Accessories Available	No
Number of Batteries	0
Connecting Capacity	Flexible 10 mm <sup>2</sup> Busbar 1 ... 25 mm <sup>2</sup> Rigid 1 ... 25 mm <sup>2</sup>
Rated Cross-Section	1 - Solid-Core 25 ... 25 mm <sup>2</sup> 4 - Multi-Wired 1 ... 25 mm <sup>2</sup>

## Material Compliance

RoHS Information	9AKK107492A8511
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20190902
REACH Declaration	9AKK108467A9482
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

## Environmental

Ambient Air Temperature	Operation -5 ... 55 °C
Degree of Protection	IP2X
Pollution Degree	2

## Dimensions

Width in Number of Modular Spacings	2
Product Net Width	0.035 m
Product Net Height	0.085 m
Product Net Depth / Length	0.069 m
Product Net Weight	0.182 kg
Built-In Depth (t <sub>2</sub> )	69 mm

---

## Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.207 kg

---

## Certificates and Declarations

Declaration of Conformity - CE	9AKK107492A8511
--------------------------------	-----------------

---

## Installation

Instructions and Manuals	9AKK107492A6712
--------------------------	-----------------

---

## Popular Downloads

Data Sheet, Technical Information	9AKK107492A6648
-----------------------------------	-----------------

---

## Classifications

ETIM 8	EC000905 - Earth leakage circuit breaker
ETIM 9	EC000905 - Earth leakage circuit breaker
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85363030
eClass	V11.0 : 27142207
Object Classification Code	F

---

## Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Circuit Breakers with Overcurrent Protection RCBO

