



 PRODUCT-DETAILS

TSM

TSM Bell



General Information

Extended Product Type	TSM
Product ID	2CSM100000R0841
EAN	8012542007005
Catalog Description	TSM Bell
Long Description	Bell characterized by discontinuous use through one or more pushbuttons, suitable for public and tertiary acoustic signalling.

Technical

Standards	EN 62080
Rated Voltage (U _r)	230 V AC
Rated Operational Voltage	230 V AC
Primary Voltage	230 V AC
Secondary Voltage	1 12 V
Rated Frequency (f)	50 Hz
	5.5 V-A
Sound / Tone Type	Intermittent

Sound dB (A)	Bell (1 m) 80 dB Buzzer (1 m) 70 dB Threetones (1 m) 84 dB
Options Provided	Transformer included
Mounting Position	Vertical only
Remarks	Discontinuous operations: the device need rest time between two consecutive functionings
Cable Cross-Section	Maximum 10 mm ²

Material Compliance

RoHS Information	2CSC446002K0201
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
RoHS Date	31/03/2006 0.00.00
REACH Declaration	9AKK108467A9482
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Degree of Protection	IP20
Environmental Information	See RoHS Information

Dimensions

Width in Number of Modular Spacings	2
Product Net Width	35 mm
Product Net Height	0.085 m
Product Net Depth / Length	0.065 m
Product Net Weight	0.300 kg

Ordering

Package Level 1 Units	box 6 piece
Package Level 1 Gross Weight	0.994 kg

Certificates and Declarations

Declaration of Conformity - CE	2CSC446011D2702
--------------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	9AKK107991A8329
-----------------------------------	-----------------

Classifications

ETIM 8	EC001547 - Bell transformer
ETIM 9	EC001547 - Bell transformer
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85043121
eClass	V11.0 : 27031190
Object Classification Code	H

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Command and Signalling Devices → Bells and Buzzers

