



PRODUCT-DETAILS

ISOLTESTER-DIG-PLUS ISOLTESTER-DIG-PLUS Insulation monitoring device for insulated network



General Information		
Extended Product Type	ISOLTESTER-DIG-PLUS	
Product ID	2CSM341000R1501	
EAN	8012542884606	
Catalog Description	ISOLTESTER-DIG-PLUS Insulation monitoring device for insulated network	
Long Description	Provide protection from indirect contacts in IT ciruits without breaking the circuit at the first indirect contact. They are used mostly in systems where residual current devices are not allowed because a sudden service breaking could cause serious inconveniences.	

Technical	
Rated Control Supply Voltage (U _s)	24230 V AC
	AtRatedLoad 6 V·A
Power Loss	4.5 W
Communication Interface	RS-485
Evaluation Inputs	Three Channel
Model Number	Basic device
Delay Time (T)	Release 00 second [unit of time]

© 2024 ABB. All rights reserved.

9AKK106713A5709
Following EU Directive 2011/65/EU
20180713
9AKK108468A3363
See RoHS Information
90 mm
0.090 m
58 mm
0.25 kg
box 1 piece
0.5 kg
2CSM257905R1501
9AKK106713A5709
9AKK107046A3890
2CSC004033B0202
EC001449 - Device for monitoring of safety-related circuits
EC001449 - Device for monitoring of safety-related circuits
5. Small Equipment (No External Dimension More Than 50 cm)
Business To Consumer
90303100 V11.0 : 27371819

Categories

Low Voltage Products and Systems \rightarrow Modular DIN Rail Products \rightarrow Protection and Safety Devices \rightarrow Hospital Equipments (H+ Line) \rightarrow Insulation Monitoring Devices for Medical Locations, ISOLTESTER - SELVTESTER - QSD









3605