
OS25FF1210-2 1/3



PRODUCT-DETAILS

## OS25FF1210-2 OS25FF1210-2 SWITCH FUSE



General Information	
Extended Product Type	OS25FF1210-2
Product ID	1SCA108801R1001
EAN	6417019420554
Catalog Description	OS25FF1210-2 SWITCH FUSE
Long Description	Switch Fuses,Front Operated,3-pole,12 (Between the Poles),NFC,10x38,Handle and shaft not included.

Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
Toxic Substances Control Act - TSCA	1SCC011025D0201

$\overline{}$			
( )	ra	eri	m
$\sim$	ıu	$\sim$ 11	

OS25FF1210-2 2/3

85365080	Customs Tariff Number
Lithuania (LT)	Country of Origin
	Popular Downloads
1SCC311013C0201	Data Sheet, Technical Information
1SCC311030M0202	Instructions and Manuals
	Dimensions
234 mm	Product Net Width
130 mm	Product Net Height
130 mm	Product Net Depth / Length
0.58 kg	Product Net Weight
	Technical
(380 415 V) 25 A	Rated Operational Current
(500 V. AC) 25 A (690 V AC) 25 A	AC-21A (I <sub>e</sub> )
(380 415 V) 25 A (500 V) 25 A (690 V) 25 A	Rated Operational Current AC-22A ( $I_e$ )
(380 415 V) 25 A (500 V) 25 A (690 V) 25 A	Rated Operational Current AC-23A (I <sub>e</sub> )
$\Theta = 40 ^{\circ}\text{C}  25  \text{A}$	Conventional Free-air Thermal Current (I <sub>th</sub> )
Fully Enclosed 25 A	Conventional Thermal Current ( $I_{the}$ )
12 kV	Rated Impulse Withstand Voltage (U <sub>imp</sub> )
1000 V	Rated Insulation Voltage $(U_i)$
Main Circuit 690 V AC	Rated Operational Voltage
for 1 s 1 kA	Rated Short-time Withstand Current Low Voltage (I <sub>cw</sub> )
(690 V) 80 kA	Rated Conditional Short- Circuit Current (I <sub>nc</sub> )
at Rated Operating Conditions per Pole 1.3 W	Power Loss
Handle and shaft not included	Handle Type
12 (Between the Poles)	Switches Operating Mechanism
Top In - Bottom Ou Bottom In - Top Ou	Position of Line Terminals
10x38	Fuse Size
NFC	Fuse System
Front Operated	Operating Mode
IEC 60947-3	Standards
Base mounting	Mounting Type
Main Circuit 25 A	Number of Poles
Main Circuit 25 A	Rated Current (I <sub>n</sub> )

_					
_	nı,	ırn	nn	na	ntal
_	IIV	11()		115	ша

RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

OS25FF1210-2 3/3

Toxic Substances Control 1SCC011025D0201
Act - TSCA

Certificates and Declarations		
Declaration of Conformity - CE	1SCC311129D2702	
DNV GL Certificate	1SCC311125D0203	
REACH Declaration	1SCC011021D0201	

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	130 mm
Package Level 1 Depth / Length	234 mm
Package Level 1 Height	130 mm
Package Level 1 Gross Weight	0.69 kg
Package Level 1 EAN	6417019420554

Classifications	
ETIM 7	EC001040 - Fuse switch disconnector
ETIM 8	EC001040 - Fuse switch disconnector
ETIM 9	EC001040 - Fuse switch disconnector
eClass	V11.1 : 27371401
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Categories

Low Voltage Products and Systems  $\rightarrow$  Switches  $\rightarrow$  Switch Fuses

