CR-M230AC2 1/4



PRODUCT-DETAILS

CR-M230AC2

CR-M230AC2 Pluggable interface relay 2c/o, A1 -A2=230VAC, 250V/12A



Extended Product Type	CR-M230AC2
Product ID	1SVR405611R3000
EAN	4013614497261

Catalog Description

CR-M230AC2 Pluggable interface relay 2c/o, A1-A2=230VAC, 250V/12A

The CR-M230AC2 pluggable interface relay is a miniature relay, which is to be plugged into a suitable ABB CR-M socket. Plugged into a socket, the combination of relay and socket may be seemlessly snap-on mounted onto a DIN Rail. This relay operates with a 230 V AC rated control supply voltage and has a 2 c/o (SPDT) output with contacts rated at 250 V / 12 A, enabling the possibility of switching multiple circuits with a single input signal. The relay has an integrated test button which is used for the manual actuation of the relay by locking it's output contacts. The test button facilitates easy testing and commissioning. The relay also has an integrated LED, which provides the visual indication of the energization of the relay coil. Standard sockets, logic sockets, pluggable function modules, holders and markers are available as accessories. Standard sockets, logical sockets, pluggable function modules, holder and marker are available as accessories.

Long Description

Ordering

EAN	4013614497261
Minimum Order Quantity	10 piece
Customs Tariff Number	85364900

CR-M230AC2 2/4

Popular Downloads	
Data Sheet, Technical Information	2CDC110004C0210_05
Instructions and Manuals	1SVC405600M9000
CAD Dimensional Drawing	2CDC001079B0201
Dimensions	
Product Net Width	21.2 mm
Product Net Height	35.6 mm
Product Net Depth / Length	27.5 mm
Product Net Weight	0.033 kg
Technical	
Function	Pluggable miniature interface relay CR-M
Sub-Function	Relay w/o built in LED
Rated Control Supply Voltage (U _s)	230 V AC
Rated Operational Voltage	250 V AC
Rated Frequency (f)	50 / 60 Hz
Output Output Signal	2 c/o (SPDT) contacts 250 V / 12 A
Terminal Type	Flat-Pin Connections
Rated Operational Current AC-12 (I _e)	(230 V) 12 A
Rated Operational Current AC-15 (I _e)	(120 V) 3 A (230 V) 1.5 A
Rated Operational Current DC-12 (I _e)	(24 V) 12 A
Rated Operational Current DC-13 (I _e)	(24 V) 2.5 A (250 V) 0.1 A
Rated Insulation Voltage (U_i)	250 V
Degree of Protection	IP40
Mounting Position Standards	1 CAN/CSA C22.2 No.14 IEC/EN 63000 IEC/EN 61810-1 UL 508
Taskaisal III (OOA	
Technical UL/CSA	
Maximum Operating Voltage UL/CSA	300 V AC
Contact Rating UL/CSA	B300
Pilot Duty UL/CSA	B300
Flammability According to UL94	НВ
Environmental	
Ambient Air Temperature	Operation -40 +55 °C Storage -40 +85 °C
Maximum Operating Altitude Permissible	Without Derating 2000 m
© 2024 ADD. All violets was and	2024/04/12

CR-M230AC2 3/4

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
RoHS Information	1SVD982021-0003
RoHS Status	Following EU Directive 2011/65/EU
Circular Value	
Environmental Information	1SAA981009-2401
Certificates and Declarations	
CCC Certificate	CCC_2014010303720193
CQC Certificate	CQC2014010303720193
CSA Certificate	CSA_2735700
cUR Certificate	cUR_E244330
Declaration of Conformity - CCC Declaration of Conformity	2020980303000200
<u>- CE</u>	1SVD982021-0003
Declaration of Conformity - UKCA	1SVD982021-1000
EAC Certificate	EAC RU C-DE.ME77.B.00446-19
RMRS Certificate	RMRS 1740019250
UR Certificate	UR_E244330
VDE Certificate	VDE 40040327
Container Information	
Package Level 1 Units	box 10 piece
Package Level 1 Width	114 mm
Package Level 1 Depth / Length	50 mm
Package Level 1 Height	61 mm
Package Level 1 Gross Weight	0.35 kg
Package Level 1 EAN	4013614373206
Classifications	
•	FC001427 Suitabina ralou
	2 ,
	2712705
	4005335
Object Classification Code ETIM 7 ETIM 8 ETIM 9 eClass UNSPSC E-Number (Finland) E-Number (Sweden)	

CR-M230AC2 4/4

Categories

 $\begin{tabular}{ll} Low Voltage Products and Systems \rightarrow Control Products \rightarrow Electronic Relays and Controls \rightarrow Interface Relays and Optocouplers \\ Medium Voltage Products and Systems \rightarrow Service \rightarrow Spares and Consumables \rightarrow Parts \rightarrow All Spare Parts (Relays-SWG-CB) \\ \end{tabular}$

