CR-M024DC2L 1/4



PRODUCT-DETAILS

CR-M024DC2L CR-M024DC2L Pluggable interface relay 2c/o, A1-A2=24VDC, 250V/12A, LED



Extended Product Type	CR-M024DC2L
Product ID	1SVR405611R1100
EAN	4013614497230

Catalog Description

CR-M024DC2L Pluggable interface relay 2c/o, A1-A2=24VDC, 250V/12A, LED

The CR-M024DC2L pluggable interface relay is a miniature relay, which is to be plugged into a suitable ABB CR-M socket. Plugged into a socket, the combination of relay and socket may be seemlessly snap-on mounted onto a DIN Rail. This relay operates with a 24 V DC rated control supply voltage and has a 2 c/o (SPDT) output with contacts rated at 250 V / 12 A, enabling the possibility of switching multiple circuits with a single input signal. The relay has an integrated test button which is used for the manual actuation of the relay by locking it's output contacts. The test button facilitates easy testing and commissioning. The relay also has an integrated LED, which provides the visual indication of the energization of the relay coil. Standard sockets, logic sockets, pluggable function modules, holders and markers are available as accessories.

Long Description

Ordering

 EAN
 4013614497230

 Minimum Order Quantity
 10 piece

 Customs Tariff Number
 85364900

CR-M024DC2L 2/4

	Popular Downloads	
2CDC110004C0210_05	Data Sheet, Technical	
15\/C40E600M0000	Information	
1SVC405600M9000 2CDC001079B0201	Instructions and Manuals CAD Dimensional	
	Drawing	
	Dimensions	
21.2 mm	Product Net Width	
35.6 mm 27.5 mm	Product Net Height Product Net Depth /	
27.3 11111	Length	
0.033 kg	Product Net Weight	
	Technical	
Pluggable miniature interface relay CR-M	Function	
Relay with built in LED 24 V DC	Sub-Function Rated Control Supply	
24 V DC	Voltage (U _s)	
250 V AC	Rated Operational Voltage	
2 c/o (SPDT) contacts 250 V / 12 A	Output	
Flat-Pin Connections	Output Signal Terminal Type	
(230 V) 12 A	Rated Operational Current AC-12 (I _e)	
(120 V) 3 A (230 V) 1.5 A	Rated Operational Current AC-15 (I _e)	
(24 V) 12 A	Rated Operational Current DC-12 (I _e)	
(24 V) 2.5 A (250 V) 0.1 A	Rated Operational Current DC-13 (I _e)	
250 V	Rated Insulation Voltage (U _i)	
IP40 1	Degree of Protection Mounting Position	
CAN/CSA C22.2 No.14 IEC/EN 63000 IEC/EN 61810-1 UL 508	Standards	
2027.42	Technical UL/CSA	
300 V AC	Maximum Operating Voltage UL/CSA	
B300	Pilot Duty UL/CSA	
НВ	Flammability According to UL94	
	Environmental	
Operation -40 +70 °C	Ambient Air Temperature	
Storage -40 +85 °C Without Derating 2000 m	Maximum Operating Altitude Permissible	

CR-M024DC2L 3/4

Material Compliance	
Conflict Minerals Reporting Template	9AKK108467A5658
(CMRT)	
RoHS Information	1SVD982021-0003
RoHS Status	Following EU Directive 2011/65/EU
Circular Value	
Environmental Information	1SAA981009-2401
Certificates and Declarations	
CCC Certificate	CCC_2014010303720193
CQC Certificate	CQC2014010303720193
CSA Certificate	CSA_2735700
cUR Certificate	cUR_E244330
Declaration of Conformity - CCC	2020980303000200
Declaration of Conformity - CE	1SVD982021-0003
Declaration of Conformity - UKCA	1SVD982021-1000
EAC Certificate	EAC RU C-DE.ME77.B.00446-19
RMRS Certificate	RMRS_1740019250
UR Certificate	UR_E244330
VDE Certificate	VDE 40040327
Container Information	
Package Level 1 Units	box 10 piece
Package Level 1 Width	114 mm
Package Level 1 Depth / Length	50 mm
Package Level 1 Height	61 mm
Package Level 1 Gross Weight	0.35 kg
Package Level 1 EAN	4013614373237

Classifications		
Object Classification C		
FTIM 7		

Object Classification Code	K
ETIM 7	EC001437 - Switching relay
ETIM 8	EC001437 - Switching relay
ETIM 9	EC001437 - Switching relay
eClass	V11.0 : 27371601
UNSPSC	39122331
E-Number (Finland)	2712657
E-Number (Sweden)	4005333

CR-M024DC2L 4/4

Categories

 $\begin{tabular}{ll} Low Voltage Products and Systems \rightarrow Control Products \rightarrow Electronic Relays and Controls \rightarrow Interface Relays and Optocouplers \\ Medium Voltage Products and Systems \rightarrow Service \rightarrow Spares and Consumables \rightarrow Parts \rightarrow All Spare Parts (Relays-SWG-CB) \\ \end{tabular}$

