MLBL-01G 1/4



PRODUCT-DETAILS

MLBL-01G MLBL-01G LED block



General Information	
Extended Product Type	MLBL-01G
Product ID	1SFA611621R1012
EAN	7320500544570
Catalog Description	MLBL-01G LED block
	The MLBL-01G LED block is: - Green - Illuminated - Front mounting - 24 V

Long Description

The MLBL-01G LED block is: - Green - Illuminated - Front mounting - 24 V
This LED block is part of ABB's modular plastic range, the most versatile range with a high
level of flexibility and market-leading electrical ratings. Engineered for total reliability, longer
lifetime, and highest mechanical durability. Self-cleaning contacts ensure reliable operation
without the need for maintenance, increasing uptime. A high degree of protection
guarantees reliability in extreme environments. The innovative design simplifies the entire
process, from selection to easy and quick, tool-free installation. The perfect solution for
every application.

	inc	

Minimum Order Quantity	10 piece
Customs Tariff Number	<u>85369001</u>

Popular Downloads

MLBL-01G 2/4

Data Sheet, Technical Information	1SFC151007C02_
Instructions and Manuals	1SFC151011M0201
Dimensions	
Product Net Width	0.01 m
Product Net Height	0.044 n
Product Net Depth / _ength	0.042 n
Product Net Weight	0.01 kg
Technical	
Ambient Air Temperature	Operation -25 +70 °C Storage -40 +85 °C
Color	Green
llumination	Illuminated
Lamp Type	24V AC / DC, integrated LED
Mounting Type	Front mounting
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	24 V AC/DC
Connecting Capacity	Flexible with Ferrule 1 x 0.752.5 mm Flexible with Ferrule 2 x 0.752.5 mm Flexible with Insulated Ferrule 1 x 0.752.5 mm Flexible with Insulated Ferrule 2 x 0.752.5 mm Flexible 1 x 0.75 2.5 mm Flexible 2 x 0.75 2.5 mm Solid 1 x 0.752.5 mm Solid 2 x 0.752.5 mm
Connection Type	Screw Clamp
Terminal Type	Screw Terminals
Fightening Torque	0.9 N·n
Vire Stripping Length	8 mm
Suitable For	MCBH-0() MCBH5-0() MP: MP: MP: MP: MP: MP: MPMT: MPMT: MPMT:
	M2SS M2SS: M2SS: M2SS: M2SS: M2SS: M3SS:
	M3SS: M3SS: M3SS: M3SS: M3SS: M3SS:
Suitable for Product Class	MPM* Pilot Devices
outable IOI FIOUUCLOIdSS	PIIOT Devices
Technical UL/CSA	
Connecting Capacity UL/CSA	1x 1814 AWG 2x 1814 AWG

MLBL-01G 3/4

Environmental	
Degree of Protection	Terminals IP20
Material Compliance	
·	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2022-006479
RoHS Information	2CMT2022-006498
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006523
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
Certificates and Declarations	
CB Certificate	SEMKO_SE-56219
CQC Certificate	CQC2008010305274953
cULus Certificate	9AKK107046A9925
Declaration of Conformity - CCC	2020980305001106
Declaration of Conformity - CE	2CMT2015-005452
Declaration of Conformity - UKCA	2CMT2020-006121
DNV GL Certificate	E-14107
EAC Certificate	1SFC150017D1101
Container Information	
Package Level 1 Units	bag 10 piece
Package Level 1 Width	0.135 m
Package Level 1 Depth / Length	0.155 m
Package Level 1 Height	0.025 m
Package Level 1 Gross Weight	0.11 kg
Package Level 1 EAN	7320500373002
Classifications	
Object Classification Code	E
ETIM 6	EC000204 - Lamp holder block for control circuit devices
ETIM 7	EC000204 - Lamp holder block for control circuit devices
ETIM 8	EC000204 - Lamp holder block for control circuit devices
eClass	V11.0 : 27371209
UNSPSC	39122221
IDEA Granular Category Code (IGCC)	5219 >> Switch part or accessory
E-Number (Finland)	2315746
E-Number (Norway)	4373119
E-Number (Sweden)	3705055

MLBL-01G 4/4

Categories

 $\begin{tabular}{ll} Low Voltage Products and Systems \rightarrow Control Products \rightarrow Pilot Devices \rightarrow Accessories \\ Low Voltage Products and Systems \rightarrow Control Products \rightarrow Pilot Devices \rightarrow Modular Plastic Range \\ Medium Voltage Products and Systems \rightarrow Service \rightarrow Spares and Consumables \rightarrow Parts \rightarrow All Spare Parts (Relays-SWG-CB) \\ \end{tabular}$







