QSD-DIG 230/24 1/3



PRODUCT-DETAILS

QSD-DIG 230/24

QSD-DIG 230/24 Remote signalling panel



General Information	
Extended Product Type	QSD-DIG 230/24
Product ID	2CSM273063R1521
EAN	8012542730637
Catalog Description	QSD-DIG 230/24 Remote signalling panel
Long Description	Remote signalling panel for visual and acoustic fault indication.

Technical	
Rated Operational Voltage	500 760 V AC
Rated Control Supply Voltage (U _s)	24 V DC
	AtRatedLoad 1 W
Model Number	Basic device
Delay Time (T)	Release 00 second [unit of time]
Mounting Orientation	Horizontal

QSD-DIG 230/24 2/3

RoHS Information	9AKK106713A5709
RoHS Status	Following EU Directive 2011/65/EI
RoHS Date	2018071
Conflict Minerals Reporting Template (CMRT)	9AKK108468A336
Environmental	
Environmental Information	See RoHS Information
Dimensions	
Product Net Width	121 mr
Product Net Height	0.078 r
Product Net Depth / Length	55 mr
Product Net Weight	0.2 k
Ordering	
Package Level 1 Units	box 1 piec
Package Level 1 Gross Weight	0.5 kg
Replacement Product ID (NEW)	2CSM257935R152
Certificates and Declarations	
Declaration of Conformity - CE	9AKK106713A570
Installation	
Instructions and Manuals	9AKK107046A389
Popular Downloads	
Data Sheet, Technical Information	2CSC004033B020
Classifications	
ETIM 8	EC001449 - Device for monitoring of safety-related circuit
ETIM 9	EC001449 - Device for monitoring of safety-related circuit
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm
WEEE B2C / B2B	Business To Consume

CN8

90303100

QSD-DIG 230/24 3/3

eClass V11.0:27371819

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Modular\ DIN\ Rail\ Products\ \rightarrow\ Protection\ and\ Safety\ Devices\ \rightarrow\ Hospital\ Equipments\ (H+Line)\ \rightarrow\ Insulation\ Monitoring\ Devices\ for\ Medical\ Locations,\ ISOLTESTER\ -\ SELVTESTER\ -\ QSD$





