




 PRODUCT-DETAILS

E 93N/125

E 93N/125 Fuse disconnecter



General Information

Extended Product Type	E 93N/125
Product ID	2CSM296532R1801
EAN	8012542965329
Catalog Description	E 93N/125 Fuse disconnecter
Long Description	E 90 50/125 fuse holders are appropriate to protect against overloads and short circuits. They are designed for use with cylindrical fuses from 50 to 125 A.

Technical

Suitable For	E 90
Suitable for Product Class	Fuse holders
Rated Voltage (U_r)	acc. To IEC 690 V acc. To UL 690 V
Rated Operational Voltage	AC-20B 690 V
Rated Insulation Voltage (U_i)	1 kV
Rated Frequency (f)	50/60 Hz

Power Loss		at Rated Operating Conditions per Pole 9.5 W
Number of Protected Poles		3
Number of Poles		4
Position of Neutral Terminals		Right
Tightening Torque		3.5...4 N·m
Utilization Category	Connecting and disconnecting under no-load conditions - occasional actuation (AC-20B)	
Lock Type		Padlockable
Mounting Type		DIN-Rail
Sealing Type		Sealing Wire
Material of Conductor		Copper
Options Provided		No
Recommended Screw Driver		Pozidriv 2
Connecting Capacity		Rigid 4...35 mm ² Rigid Stranded 4...50 mm ²
Fuse Size		22x58 mm
Rated Operational Current AC (I _e)		max. 90% with temp. +20 °C 50% with max. temp. +40 °C 125 A

Material Compliance

RoHS Information		2CSC444009D2701
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019	
RoHS Date		01/01/2014 0.00.00
REACH Declaration		9AKK108467A9482
Conflict Minerals Reporting Template (CMRT)		9AKK108468A3363

Environmental

Ambient Air Temperature		Storage -5...+40 °C Storage Operation -25...+70 °C
Degree of Protection		IP20
Resistance to Vibrations		1 mm 2 ... 13 Hz
Resistance to Shock acc. to IEC 60068-2-27		15g 18 shocks 11 ms
Environmental Information		See RoHS Information

Dimensions

Width in Number of Modular Spacings		8
Product Net Width		0.140 m
Product Net Height		0.112 m
Product Net Depth / Length		0.07326 m
Product Net Weight		0.54 kg
Built-In Depth (t ₂)		73.26 mm

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.54 kg

Certificates and Declarations

BV Certificate	9AKK108467A0329
CCC Certificate	9AKK108467A0344
Certification Agency	BV, Korean register, CCC, EAC, UL
Declaration of Conformity - CE	2CSC444009D2701
KRS Certificate	9AKK108467A0338
LR Certificate	9AKK108467A0332
RINA Certificate	9AKK107992A0866
UL Certificate	9AKK107992A1042

Installation

Instructions and Manuals	No document needed
--------------------------	--------------------

Popular Downloads

Data Sheet, Technical Information	2CSC444002B0204
-----------------------------------	-----------------

Classifications

ETIM 8	EC002705 - Holder for cylindrical fuse
ETIM 9	EC002705 - Holder for cylindrical fuse
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85361090
UNSPSC	39121624
eClass	V11.0 : 27142121
IDEA Granular Category Code (IGCC)	4974 >> Holder for cylindrical fuse
Object Classification Code	F

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CSM257183R1801	E 9F22 GG4 Fuse link	E 9F22 GG4	1	piece
2CSM259283R1801	E 9F22 GG6 Fuse link	E 9F22 GG6	1	piece
2CSM258103R1801	E 9F22 GG8 Fuse link	E 9F22 GG8	1	piece
2CSM256923R1801	E 9F22 GG10 Fuse link	E 9F22 GG10	1	piece
2CSM259403R1801	E 9F22 GG12 Fuse link	E 9F22 GG12	1	piece
2CSM258223R1801	E 9F22 GG16 Fuse link	E 9F22 GG16	1	piece
2CSM257043R1801	E 9F22 GG20 Fuse link	E 9F22 GG20	1	piece
2CSM259533R1801	E 9F22 GG25 Fuse link	E 9F22 GG25	1	piece
2CSM258353R1801	E 9F22 GG32 Fuse link	E 9F22 GG32	1	piece
2CSM257173R1801	E 9F22 GG40 Fuse link	E 9F22 GG40	1	piece
2CSM259393R1801	E 9F22 GG50 Fuse link	E 9F22 GG50	1	piece
2CSM258213R1801	E 9F22 GG63 Fuse link	E 9F22 GG63	1	piece
2CSM257033R1801	E 9F22 GG80 Fuse link	E 9F22 GG80	1	piece
2CSM259523R1801	E 9F22 GG100 Fuse link	E 9F22 GG100	1	piece
2CSM258343R1801	E 9F22 GG125 Fuse link	E 9F22 GG125	1	piece

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Protection and Safety Devices → Cylindrical Fuse Holders and Fuse Switch Disconnectors

