

## Coperchi trasparenti IP55 a tenuta d'aria

### IP55 Windproof transparent lids

	Descrizione Description	Info	€	□	□
	<b>BLST05TR</b> Coperchio trasparente stagno per scatola BL05P - dimensioni (L H P): 184x153x4,5 mm <i>Transparent splash proof lid for BL05P box - dimensions (L H D): 184x153x4,5 mm</i>		1	40	
<b>BLST05TR</b>					
	<b>BLST06TR</b> Coperchio trasparente stagno per scatola BL06P - dimensioni (L H P): 207x184x4,5 mm <i>Transparent splash proof lid for BL06P box - dimensions (L H D): 207x184x4,5 mm</i>		1	30	
<b>BLST06TR</b>					
	<b>GWEPT</b> (resistenza al fuoco): 850°C - <b>Resistenza agli urti:</b> IK 10 <b>GWEPT</b> (flame resistance): 850°C - <b>Shock resistance:</b> IK 10				
	<b>Note:</b> ✓ coperchi dotati di guarnizione siliconica <b>Note:</b> ✓ lids equipped with silicone gasket				
		Certificati pag. 648 Certificates page 648			

## Accessori Accessories

	Descrizione Description	Info	€	□	□
	<b>BLAS1</b> Dispositivo di accoppiamento per scatole: BL01P/BL05P/BL06P BL07P/BL08P/BL08LP/ BL09P/BL10S/BL18S/53S36 <i>Box coupler to be used with: BL01P/BL05P/BL06P/BL07P/BL08P BL08LP/ BL09P/BL10S/BL18S/53S36</i>		20	20	
<b>BLAS1</b>					
	<b>BLAS2</b> Dispositivo di accoppiamento per scatole: 2503MG/SFM3 2504/2506/BL02P/BL03P/BL04P <i>Box coupler for boxes: 2503MG/SFM3/2504 2506/BL02P/BL03P/BL04P</i>		20	20	
<b>BLAS2</b>					
	<b>BLAS25</b> Dispositivo di accoppiamento per scatole: 2503MG/SFM3/2504/2506/BL02P/BL03P/BL04P <i>Box coupler to be used with: 2503MG/SFM3/2504/2506/BL02P/BL03P/BL04P</i>		20	20	
<b>BLAS25</b>					
	<b>BLS08</b> Setto separatore per scatole: BL05P/BL06P/BL07P/BL08P/BL08LP/BL09P/BL10S <i>Clip-in divider for boxes: BL05P/BL06P/BL07P/BL08P/BL08LP/BL09P/BL10S</i>		10	10	
<b>BLS08</b>					
	<b>25TTC20</b> Tappo per tubo corrugato Ø 20 mm <i>Plug for corrugated duct Ø 20 mm</i>		20	20	
<b>25TTC20</b>					
	<b>25TTC25</b> Tappo per tubo corrugato Ø 25 mm <i>Plug for corrugated duct Ø 25 mm</i>		20	20	
<b>25TTC25</b>					
	<b>25TTC32</b> Tappo per tubo corrugato Ø 32 mm <i>Plug for corrugated duct Ø 32 mm</i>		20	20	
<b>25TTC32</b>					
	<b>BLS08</b>				
	<b>BLV0960</b> Vite per coperchi scatole di derivazione serie BL - lunghezza = 25mm <i>Screw for BL series lids - length= 25mm</i>		200	200	
<b>BLV0960</b>					
	<b>012DR</b> Morsettiera per terra o neutro 12 poli per scatole di derivazione a partire da BL05P <i>12 way earth/neutral terminal bar for junction boxes starting from BL05P</i>		1	1	
<b>012DR</b>					

 TÜVRheinland®  
Certificati pag. 648  
Certificates page 648