




**Coprisbarre, 12-30x10, L=1m**



Powering Business Worldwide™

**Tipo** **BBC-FL10**  
**Catalog No.** **107174**

## Programma di fornitura

			
Assortimento			sistema 60-mm sistema 185-mm Sistema Compact
Sotto gamma			Coperture per sbarre
Materiale			senza silicone, senza cloro
autoestinguente			secondo UL 94
Resistente alla temperatura			a 110°C
Lunghezza		mm	1000
utilizzo con			12 x 10 15 x 10 20 x 10 25 x 10 30 x 10
utilizzabile per			Tutte le sbarre piatte con spessore 10 mm

## Dati tecnici secondo ETIM 8.0

sistemi di distribuzione dell'energia/apparecchi elettrici (EG000015) / Accessori per sbarra collettrice (EC002270)			
Tecnica Di Ar., Elettr., Energia, Tecn. Di Comm., Rete E Proc. Di Conduttura / Materiale Elettrico Di Isolamento E Collegamento / Energy distribution system / Busbar (accessories) (ecl@ss10.0.1-27-40-06-36 [AC0563011])			
tipologia accessorio			schermatura guida
Accessorio			si
Pezzo di ricambio			si

## Approvazioni

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E300273
UL Category Control No.			NMTR, NMTR7
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL listed, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits