

Data sheet

050ASPLD01

Dispositivo di sicurezza monofase lampeggiante, con led rosso 24V, AC/DC, 1 N.C.



Features

Range	050 Segnalazione ed Illuminazione Quadri Elettrici
Product	Dispositivi di sicurezza lampeggianti
Type	Dispositivi di sicurezza monofase lampeggianti
Item code	050ASPLD01
Description	Dispositivo di sicurezza monofase lampeggiante, con led rosso 24V, AC/DC, 1 N.C.
Colour	Rosso
Weight - gr	115,000
Custom tariff no.	85365080
GTIN	8052878048594

Technical data

Approvals	CE
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +65°C
Environmental operating values	"all climates" +40°C and 92% RH
Protection degree	IP20 (IEC-EN60529)
Protection against impact	IK03 (IEC-EN62262)
Mechanical durability	1.000.000 Operations
Shock resistance	30g duration=18ms (EN-IEC 60068-2-27)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Vibration resistance	5g f= 2...500Hz (EN-IEC 60068-2-6)
Contact blocks configuration	Max no. 2 blocks (1+1)
Material	PA Polyamide
Lens material	PC Polycarbonate
Locking ring material	ZAMAK zinc alloy
Actuation type	Spring return
Rated insulation voltage	Ui 690V - Uimp 4kV (IEC-EN60947-1)
Overtoltage category	Class II (IEC-EN61140)
Signalling type	Flashing
Led bulb type	Ba9S red flashing bulb 24V AC/DC included
Model 050ASPD11 without Ba9s Led bulb	Customizable with appropriate Led voltage
Contact block characteristics	See items: 020PD911,020PD901, 020PD910
Warranty period	18 months

Data sheet

050ASPLD01

Dispositivo di sicurezza monofase lampeggiante, con led rosso 24V, AC/DC, 1 N.C.

Technical drawings

