

# Buffer Tube Fan-Out Kits, Indoor

12 F, 1138 mm legs

CORNING

Corning Cable Systems Indoor Buffer Tube Fan-Out Kits are specifically designed for the termination of 6- and 12-fibre buffer tubes. These buffer tube fan-out kits provide the ultimate solution for those users who want to field-install connectors on 250 µm coated fibres. The kits provide the most compact, easy-to-install fan-out solution requiring no additional hardware or space than that required for terminating tight-buffered cables. Indoor Kits feature a 900 µm Fan-Out Assembly that is color-coded to match the fibre color scheme. The Fan-Out Assembly is available with 6- or 12-fibre units in lengths of 0.6 m (25-in) or 1.2 m (47-in). These different lengths provide the installer the flexibility needed for a variety of hardware options.

## Features and Benefits

### Snap-together furcation


Eliminates epoxy for indoor kits

### Fiber routing capabilities

Better fiber management

### Compensation for wide temperature fluctuation

Outdoor use



Part Number: FAN-BT47-12

## Specifications

General Specifications	
Environment	Indoor
Fanout Type	Buffer Tube
Product Type	Fan-Out Kits

Temperature Range	
Operation	0 °C to 70 °C (32 °F to 158 °F)



# Buffer Tube Fan-Out Kits, Indoor

12 F, 1138 mm legs

CORNING

Design	
Cable Type	Cable with 250 µm fiber
Fibre Count	12
Fan-out tubing colour	Blue, orange, green, brown, grey, white, red, black, yellow, violet, pink, turquoise

Mechanical Specifications - Fan-Out Kit	
Furcation length	44.5 mm (1.75 in)
Tubing length	1193.8 mm (47 in)
Tubing outer diameter	0.9 mm

Chemical characteristics	
RoHS	Free of hazardous substances according to RoHS 2002/95/EG

## Ordering Information

Order Number	FAN-BT47-12
Product Description	Buffer Tube Fan-Out Kit, indoor, 12 F, 1138 mm legs

## Shipping Information

Units per Delivery	1/1
Package Contents	Fan-out top, fan-out bottom, insert with fan-out tubing

Corning Cable Systems GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, Germany

TEL: 00800-2676-4641 (00800-CORNING1) · FAX: +49-30-5303-2335 · [www.corning.com/cablesystems/emea](http://www.corning.com/cablesystems/emea)

A complete listing of the trademarks of Corning Cable Systems is available at [www.corning.com/cablesystems/emea/trademarks](http://www.corning.com/cablesystems/emea/trademarks). Corning Cable Systems is ISO 9001 certified. © 2012 Corning Cable Systems. All rights reserved.