

## Piastra con morsetti 16 mm<sup>2</sup>, 3p (01592)



### Descrizione

#### Articolo

Cod.art.: 01592

CRITO<sup>®</sup> CrossBoard

Piastra con morsetti 16 mm<sup>2</sup>, 3p

largh. 18mm, morsetti a molla 1,5 - 16 mm<sup>2</sup>, AWG 14 - 6

#### Montaggio

CrossBoard<sup>®</sup>

Gruppo di prodotti 07

Sottogruppo merceologico 40

Pz / conf. 1

EAN 4021267015923

Catalog page 2018 : 1.1

eCl@ss 6.1 27141146  
27141146  
ETIM 4.0 EC000001  
ETIM 5.0 EC000001

## Certificazioni

### Norme

IEC 61439-1:2011  
IEC 60999-1:1999  
IEC 60999-2:2003

### Omologazioni

IEC (CB) , UL



for UL feeder circuits >250V

Type No.: CR22-A

UL file: E123577, UL category (for USA): NMTR <http://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR7 <http://www.ul.com>

Omologazione CCC : no certification required

## Dati prodotto

### Valori elettrici

Corrente nominale (IEC): 63 A

Tensione nominale (IEC) AC: 690  
V

Rated current (UL): 48 A

Rated voltage (UL) AC: 600  
V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 2.9 W.

(The power dissipation for operation with rated current would be 4.6 W.)

Utilizzabile fino a max. (IEC): 80 A

rated isolation voltage  $U_j$ : 1000  
V  
Tensione di picco  $U_{imp}$ : 6 kV  
Tensione max. IEC AC: 1000  
V  
Tensione max. IEC DC: 1000  
V

rated peak withstand current  $I_{pk}$ : 10 kA

SCCR: 6 kA

SCCR: 50kA @ fuse Class J 60A, 600Vac

### Valori meccanici

L x H x P: 22.5 x 160 x 115

Peso: 21.5 kg/100

Poli: 3 poli

### Conessioni

For leads per IEC :

1.5 - 16 mm<sup>2</sup> round stranded and finely stranded without wire-end ferrule

1.5 - 16 mm<sup>2</sup> finely stranded with wire-end ferrule\*

1.5 - 10 mm<sup>2</sup> finely stranded with wire-end ferrule

1.5 - 10 mm<sup>2</sup> round solid

\* Recommendation: 16 mm<sup>2</sup> crimped with Rittal crimping pliers for wire-end ferrules WM-Crimp, Weidmüller crimping tool PZ 16 or Phoenix Contact crimping pliers Crimpfox 25R

for leads per UL:

Cu AWG 14 - 6

Class B (UL486E)

### Proprietà materiali

Corpo temperature stability 125°C,

base: self-extinguishing in acc. to UL 94,

creepage resistance CTI 600,

halogen-free