

Piastra con morsetti di connessione, 3 poli (01754)



Descrizione

Articolo

Cod.art.: 01754

CRITO® 60Classic

Piastra con morsetti di connessione, 3 poli

95 - 300 mm²

per barre 20, 25, 30 x 5, 10 e barre profilate

Montaggio

60Classic

Gruppo di prodotti 07

Sottogruppo merceologico 51

Pz / conf. 1

EAN 4021267017545

Vantaggi prodotto

Terminals with captive clamping screws

Conductor can be overlapped

Indication of nominal cross-section and tightening torque noted on the terminals.

Catalog page 2018 : 3.5

eCl@ss 6.1 27141146
27141146

ETIM 4.0 EC000001

ETIM 5.0 EC000001

Certificazioni

Norme

IEC 61439-1:2011

IEC 60999-1:1999

IEC 60999-2:2003

Omologazioni

Germanischer Lloyd



Type No.: 413

Omologazione CCC : no certification required

Dati prodotto

Valori elettrici

Corrente nominale (IEC): 500 A

Tensione nominale (IEC) AC: 690 V

Utilizzabile fino a max. (IEC): 560 A

rated isolation voltage U_j : 800
V
Tensione di picco U_{imp} : 6 kV
Tensione max. IEC AC: 800
V
Tensione max. IEC DC: 800
V

rated peak withstand current I_{pk} : 63.1 kA

Valori meccanici

L x H x P: 135 x 200 x 118
Peso: 165.7 kg/100
Poli: 3 poli
per barre: 20, 25, 30 x 5, 10 e barre profilate

Connessioni

for applications acc. to IEC / EN :

Cu 95 - 300 mm² stranded round cables and stranded sectored cables as well as flexible cables (directly)

Al 120 - 300 mm² stranded round cables and stranded sectored cables

Al 120 - 240 mm² solid sectored cables

for applications acc. to UL / CSA :

Cu 95 - 300 mm² / AWG 3/0 - MCM 600

Suitable for aluminium cables.

Connections with aluminium cables are not maintenance-free.

Proprietà materiali

Corpo: temperature stability 125°C,
base: self-extinguishing in acc. to UL 94,
creepage resistance CTI 200,
halogen-free
Copertura: temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 200,
halogen-free

Terminals: galvanised steel, chromited screw: hexagon socket screw, galvanised, chromited, thrust piece
brass, nickel-plated

Altre versioni

Part no. 01 199 connecting terminal plate for round conductors 95-185mm²

Part no. 01 753 connecting terminal plate for flat conductors 32x20